



# PANELRADIATORER




**COPA**  
RADIATORER

# 1 TYPE 11

= Lagervarer

| Lgd/mm | Hd/mm | 300 | 400 | 500  | 600  | 750  | 900  |
|--------|-------|-----|-----|------|------|------|------|
| 300    | Watt: | 88  | 98  | 119  | 138  | 165  | 191  |
| 400    | Watt: | 118 | 131 | 159  | 184  | 219  | 255  |
| 500    | Watt: | 147 | 164 | 198  | 231  | 274  | 318  |
| 600    | Watt: | 177 | 197 | 238  | 277  | 329  | 382  |
| 700    | Watt: | 206 | 230 | 278  | 323  | 384  | 445  |
| 800    | Watt: | 236 | 263 | 317  | 369  | 439  | 509  |
| 900    | Watt: | 265 | 295 | 357  | 415  | 494  | 573  |
| 1000   | Watt: | 295 | 328 | 396  | 461  | 549  | 636  |
| 1100   | Watt: | 324 | 361 | 436  | 507  | 604  | 700  |
| 1200   | Watt: | 354 | 394 | 476  | 553  | 658  | 764  |
| 1400   | Watt: | 413 | 460 | 555  | 645  | 768  | 891  |
| 1500   | Watt: | 443 | 493 | 595  | 692  | 823  | 955  |
| 1600   | Watt: | 472 | 525 | 634  | 738  | 878  | 1018 |
| 1800   | Watt: | 531 | 591 | 714  | 830  | 988  | 1145 |
| 2000   | Watt: | 590 | 657 | 793  | 922  | 1097 | 1273 |
| 2200   | Watt: | 649 | 722 | 872  | 1014 | 1207 | 1400 |
| 2500   | Watt: | 738 | 821 | 992  | 1153 | 1372 | 1596 |
| 2600   | Watt: | 767 | 854 | 1031 | 1199 | 1427 | 1655 |
| 3000   | Watt: | 885 | 985 | 1189 | 1383 | 1646 | 1909 |

Temperatursæt 60/40/20



Anboringer: 4 x 1/2"  
 Farve: RAL 9016  
 Max. driftstryk: 10 bar.  
 Prøvetryk: 13 bar.  
 L-vægkonsol: 2 afstandsmuligheder:  
 30 eller 45 mm


|                |     |     |     |     |     |     |
|----------------|-----|-----|-----|-----|-----|-----|
| A              | 300 | 400 | 500 | 600 | 750 | 900 |
| B              | 245 | 345 | 445 | 545 | 695 | 845 |
| C              | 50  |     |     |     |     |     |
| D              | 17  |     |     |     |     |     |
| Alle tal er mm |     |     |     |     |     |     |

Alle radiatorer leveres med vægkonsoller, luftskruer og prop.  
 NB: Leveringstid på panelradiatorer ud over lagerprogram er ca. 9 uger.

# TYPE 21

= Lagervarer **2**

| Lgd/mm | Hd/mm | 300  | 400  | 500  | 600  | 750  | 900  |
|--------|-------|------|------|------|------|------|------|
| 300    | Watt: | 119  | 151  | 179  | 205  | 238  | 271  |
| 400    | Watt: | 159  | 201  | 239  | 273  | 317  | 361  |
| 500    | Watt: | 199  | 251  | 298  | 341  | 396  | 451  |
| 600    | Watt: | 238  | 301  | 358  | 409  | 475  | 541  |
| 700    | Watt: | 278  | 351  | 418  | 478  | 554  | 631  |
| 800    | Watt: | 318  | 401  | 477  | 546  | 634  | 722  |
| 900    | Watt: | 358  | 452  | 537  | 614  | 713  | 812  |
| 1000   | Watt: | 397  | 502  | 597  | 682  | 792  | 902  |
| 1100   | Watt: | 437  | 552  | 656  | 750  | 871  | 992  |
| 1200   | Watt: | 477  | 602  | 716  | 819  | 950  | 1082 |
| 1300   | Watt: | 517  | 653  | 776  | 887  | 1030 | 1173 |
| 1400   | Watt: | 556  | 703  | 835  | 955  | 1109 | 1263 |
| 1500   | Watt: | 596  | 763  | 895  | 1023 | 1188 | 1353 |
| 1600   | Watt: | 636  | 803  | 955  | 1091 | 1267 | 1443 |
| 1800   | Watt: | 715  | 903  | 1074 | 1228 | 1426 | 1624 |
| 2000   | Watt: | 795  | 1004 | 1193 | 1364 | 1584 | 1804 |
| 2200   | Watt: | 874  | 1104 | 1313 | 1501 | 1743 | 1984 |
| 2500   | Watt: | 993  | 1255 | 1492 | 1706 | 1980 | 2255 |
| 2600   | Watt: | 1033 | 1305 | 1551 | 1774 | 2059 | 2345 |
| 3000   | Watt: | 1192 | 1505 | 1790 | 2046 | 2376 | 2706 |



## Temperatursæt 60/40/20

Anboringer: 4 x 1/2"  
 Farve: RAL 9016  
 Max. driftstryk: 10 bar.  
 Prøvetryk: 13 bar.  
 L-vægkonsol: 2 afstandsmuligheder:  
 30 eller 45 mm

|   |     |     |     |     |     |     |
|---|-----|-----|-----|-----|-----|-----|
| A | 300 | 400 | 500 | 600 | 750 | 900 |
| B | 245 | 345 | 445 | 545 | 695 | 845 |
| C | 70  |     |     |     |     |     |
| D | 35  |     |     |     |     |     |


Alle tal er mm

Alle priser er bruttopriser ex. moms. Ret til ændringer forbeholdes.  
 NB: Leveringstid på panelradiatorer ud over lagerprogram er ca. 9 uger.

# 3 TYPE 22

= Lagervarer

| Lgd/mm | Hd/mm | 300  | 400  | 500  | 600  | 750  | 900  |
|--------|-------|------|------|------|------|------|------|
| 300    | Watt: | 154  | 194  | 231  | 265  | 309  | 353  |
| 400    | Watt: | 205  | 259  | 309  | 354  | 412  | 471  |
| 500    | Watt: | 256  | 324  | 386  | 442  | 516  | 589  |
| 600    | Watt: | 307  | 389  | 463  | 531  | 619  | 707  |
| 700    | Watt: | 359  | 453  | 540  | 619  | 722  | 825  |
| 800    | Watt: | 410  | 518  | 617  | 707  | 825  | 942  |
| 900    | Watt: | 461  | 583  | 694  | 796  | 928  | 1060 |
| 1000   | Watt: | 512  | 648  | 772  | 884  | 1031 | 1178 |
| 1100   | Watt: | 563  | 713  | 849  | 973  | 1134 | 1296 |
| 1200   | Watt: | 615  | 777  | 926  | 1061 | 1237 | 1414 |
| 1300   | Watt: | 666  | 842  | 1003 | 1150 | 1341 | 1532 |
| 1400   | Watt: | 717  | 907  | 1080 | 1238 | 1444 | 1649 |
| 1500   | Watt: | 768  | 972  | 1158 | 1327 | 1547 | 1767 |
| 1600   | Watt: | 819  | 1037 | 1235 | 1415 | 1650 | 1885 |
| 1800   | Watt: | 922  | 1166 | 1389 | 1592 | 1856 | 2120 |
| 2000   | Watt: | 1024 | 1296 | 1543 | 1769 | 2062 | 2356 |
| 2200   | Watt: | 1127 | 1425 | 1698 | 1945 | 2269 | 2592 |
| 2500   | Watt: | 1276 | 1620 | 1929 | 2211 | 2578 | 2945 |
| 2600   | Watt: | 1332 | 1684 | 2006 | 2299 | 2681 | 3063 |
| 3000   | Watt: | 1537 | 1943 | 2315 | 2653 | 3093 | 3534 |



Temperatursæt 60/40/20

Anbringer: 4 x 1/2"  
 Farve: RAL 9016  
 Max. driftstryk: 10 bar.  
 Prøvetryk: 13 bar.  
 L-vægkonsol: 2 afstandsmuligheder:  
 30 eller 45 mm


|                |      |     |     |     |     |     |
|----------------|------|-----|-----|-----|-----|-----|
| A              | 300  | 400 | 500 | 600 | 750 | 900 |
| B              | 245  | 345 | 445 | 545 | 695 | 845 |
| C              | 104  |     |     |     |     |     |
| D              | 52,5 |     |     |     |     |     |
| Alle tal er mm |      |     |     |     |     |     |

Alle priser er bruttopriser ex. moms. Ret til ændringer forbeholdes.  
 NB: Leveringstid på panelradiatorer ud over lagerprogram er ca. 9 uger.

# TYPE 33

  = Lagervarer 4

| Lgd/mm | Hd/mm | 300  | 400  | 500  | 600  | 750  | 900  |
|--------|-------|------|------|------|------|------|------|
| 300    | Watt: | 220  | 277  | 330  | 379  | 447  | 516  |
| 400    | Watt: | 293  | 369  | 440  | 505  | 597  | 688  |
| 500    | Watt: | 366  | 462  | 550  | 631  | 746  | 860  |
| 600    | Watt: | 439  | 554  | 660  | 758  | 895  | 1032 |
| 700    | Watt: | 513  | 647  | 770  | 884  | 1044 | 1204 |
| 800    | Watt: | 586  | 739  | 880  | 1010 | 1193 | 1376 |
| 900    | Watt: | 659  | 831  | 990  | 1137 | 1342 | 1548 |
| 1000   | Watt: | 732  | 924  | 1100 | 1263 | 1491 | 1720 |
| 1100   | Watt: | 806  | 1016 | 1210 | 1389 | 1640 | 1891 |
| 1200   | Watt: | 879  | 1108 | 1320 | 1516 | 1790 | 2063 |
| 1300   | Watt: | 952  | 1201 | 1430 | 1642 | 1939 | 2235 |
| 1400   | Watt: | 1025 | 1293 | 1540 | 1768 | 2088 | 2407 |
| 1500   | Watt: | 1099 | 1386 | 1650 | 1895 | 2237 | 2579 |
| 1600   | Watt: | 1172 | 1478 | 1760 | 2021 | 2386 | 2751 |
| 1800   | Watt: | 1318 | 1663 | 1980 | 2273 | 2684 | 3095 |
| 2000   | Watt: | 1465 | 1847 | 2200 | 2526 | 2983 | 3439 |
| 2200   | Watt: | 1611 | 2032 | 2420 | 2779 | 3281 | 3783 |
| 2500   | Watt: | 1831 | 2310 | 2751 | 3158 | 3728 | 4299 |
| 2600   | Watt: | 1904 | 2402 | 2860 | 3284 | 3877 | 4471 |
| 3000   | Watt: | 2197 | 2771 | 3300 | 3789 | 4474 | 5159 |



## Temperatursæt 60/40/20

Anbringer: 4 x 1/2"  
 Farve: RAL 9016  
 Max. driftstryk: 10 bar.  
 Prøvetryk: 13 bar.  
 L-vægkonsol: 2 afstandsmuligheder:  
 30 eller 45 mm

|                |      |     |     |     |     |     |
|----------------|------|-----|-----|-----|-----|-----|
| A              | 300  | 400 | 500 | 600 | 750 | 900 |
| B              | 245  | 345 | 445 | 545 | 695 | 845 |
| C              | 160  |     |     |     |     |     |
| D              | 52,5 |     |     |     |     |     |
| Alle tal er mm |      |     |     |     |     |     |

NB: Leveringstid på panelradiatorer ud over lagerprogram er ca. 9 uger.



## Radiatorforskruing - 1/2"

40 5000 004 - lige  
40 5001 004 - vinkel



## 1'er bøjning - fornicket - 1/2"

40 5024 004



## Exentriker - N/N - 1/2"

32 0095 104 - 10 mm pr. stk.  
32 0095 204 - 20 mm pr. stk.  
32 0095 304 - 30 mm pr. stk.  
32 0095 404 - 40 mm pr. stk.  
32 0095 504 - 50 mm pr. stk.  
32 0095 704 - 75 mm pr. stk.



## Klemring t/ kobber- & stålror

40 1790 922 3/8" - 12 mm  
40 1790 923 1/2" - 12 mm  
40 1790 925 1/2" - 15 mm



## Eksklusiv aftappingsventil.

40 5642 304 pr. stk.

## Nippel muffe 1/2" - 3/8"

40 5005 026 pr. stk.



## Samleled til radiator

O1019304  
3/4" union - 2 x 1/2" - fornicket  
O1028161  
Nippel 1/2" - 1/4"



## Gulvben t/panelradiatorer

G940 Uni- standard pr. stk.  
G940 Raw  
- ekstra høj (300 mm) pr. stk.



## Rosette t/ gulvben

Ros940Uni pr. stk.



## L-vægkonsol

950002-3/4/5/6/7/9 pr. stk.



## L-Konsol m/ afstandsstykke

950005-W pr. sæt



## Klikbæring

300-400-500 mm  
600-750-900 mm pr. stk.  
1600-1800-2000 mm pr. stk.



**Oventrop - ventiler - 1/2"**  
**AV9 forindst. - M30 x 1 1/2"**

O1183704 - vinkel pr. stk.  
O1183804 - lige pr. stk.  
O1183904 - omv. Vinkell. pr. stk.



**Oventrop - ventiler - 1/2"**  
**uden forindst. - stort flow - M30 x 1 1/2"**

O1181004 - vinkel pr. stk.  
O1181104 - lige pr. stk.  
O1181404 - omv. Vinkell. pr. stk.



**Oventrop - føler M30 x 1 1/2"**

O1011465 - Uni LH pr. stk.  
O1013066 - Vindo TH pr. stk.



**Danfoss ventil RA-N - 1/2"**

40 3202 004 - lige pr. stk.  
40 3204 004 - vinkel pr. stk.  
40 3205 004 - omv. Vinkell. pr. stk.



**Danfoss ventil RA-G - 1-streghs - 1/2"**

40 3282 104 - lige  
40 3283 104 - vinkel



**Danfoss - føler snap**

40 3222 100 - RA 2990 pr. stk.



**Oventrop - føler t/ danfoss snap ventiler**

O1011475 - Uni LD pr. stk.  
O1013076 - Vindo LD pr. stk.



**Fjernfølere**

Danfoss RA 2992  
40 3224 100 pr. stk.



Oventrop LH - 2mt. - M30 x 1 1/2"  
O1011665 pr. stk.



Oventrop FH -termostat med fjernbetj. - 2 mtr.  
O1012295 pr. stk.



MH CON - telestat m/batteri"  
O1150665 pr. stk.

R Tronic - rumføler m/display  
O1150680 pr. stk.